


Technical information sheet

Leadax LRS (+ Ridge attachment)



Date of printing: 17-10-2022, version 1.0

1. Product description

The Leadax Reinforced Strip (LRS) is intended for ridge attachment and fastening of the underlying mechanism without perforation of the roof membrane.

2. Applications

The Leadax LRS strip was designed for mechanically fastening the Leadax Roov membrane in all systems along the surface, straight edges, skylights and inner walls. This is the standard method for executing a ridge attachment. The strip can also be used on the flat section in order to mechanically fasten the roof surface.

3. Preparation

Always make sure the surface is dry, clean, free of dust and flat before commencing the works. Check slope, flatness, smoothness and suitability.

4. Instructions for use

The Leadax strip is rolled out alongside the edge and can be attached both to the edge and the roof surface. The choice of either vertical or horizontal attachment is partially determined by the processing difficulty (nature of the surface, insulation thickness, etc.). If possible, vertical attachment is preferred.

Place the ridge attachment strip as close to the angle change as possible. Ensure that the strip is flat and free of creases. Leave no more than 10 mm between the ridge attachment strip and the edge. If this is impossible, contact the Leadax technical department.

Place the plate/tulle and fasteners as indicated on the section of the ridge attachment strip, as flat as possible and 30 mm away from the edge.

For specific details, please refer to the processing instructions. See chapter 3.3.2

5. Safety instructions

Not applicable.

Technical information sheet

Leadax LRS (+ Ridge attachment)

6. Handling and storage

- All Leadax LRS rolls must be stored vertically on a clean and flat surface away from direct heat sources.
- It is not permitted to stack pallets with Leadax LRS rolls (!).
- If indoor storage is impossible, the rolls and their accessories must be kept dry, without any exposure to direct sunlight and sufficiently secured and protected.
- The ideal storage temperature for all materials is between 10°C (50°F) and 25°C (77 °F).

7. Packaging and lifespan

Material	Contents	Lifespan
r-PVB	Roll	At least 30 years

8. Technical details

Summary	r-PVB
Colour	Transparant
Dimensions	15m x ± 0.20m (49,21ft x 0,66ft)
Thickness	± 1.9 mm (74.8 mil)

The typical properties in this document are derived from standard product tolerances and should not be considered as specifications. No variations in product performance are expected during standard production processes. The information in this document may be altered without product presentations.

Leadax Circular Roofing B.V.
Ingenieur R.R. van der Zeelaan 10
8191 HZ, Wapenveld, the Netherlands
+31 (0)38 337 21 00 / www.leadax.com
